

## MC010 ALU BLUE

350mA Blue Quicklink: Q2720

## General

Cerrerai	
Colour	Aluminium
Construction	Aluminium
Dimmable	Yes
IP Rating	IP65
Dimmable	Yes
Dimensions	
Cut Out	20mm (Diameter)
	54mm
Depth	-
Height	34mm
Width	34mm
Electrical	
Maximum Wattage	1W

## **Light Characteristics**

Beam Angle	30°
Lux At 1m	201

The **Mini Cube LED Wall Light** features a single (MC010) spot lens creating an incredible light effect on the wall above or below it. IP65 rated allowing it to be installed in bathrooms, easy to install, low running costs and very reliable.

## LED Driver Options

- LED Driver (Switching) Use this driver for on/off control. Cannot be used for dimming.
- LED Driver (Dimming) For use with nearly all domestic dimming lighting. Most resistive dimmers have a minimum load of 60W, therefore ensure that if this not met, a dummy load is added to the circuit, such as a mains voltage halogen fitting.
- LED Driver (1-10V) For use with 1-10V dimmer modules or 1-10V control systems. This type of dimming does not have a minimum load.
- Wise Chameleon (Dimming + Wireless) This controller can be used for both switching and dimming. Additionally, this unit can communicate via radio and external push buttons, allowing you to wirelessly control your fitting. Note that an additional 24V LED driver is required to power the Wise Chameleon pack.