



MC020 ALU C/W

350mA 4000K Cool White Quicklink: Q2724

General

Colour Aluminium
Construction Aluminium

Dimmable Yes IP Rating IP 65

Dimmable Yes

Dimensions

Cut Out 20mm (Diameter)

Depth 54mm Height 58mm Width 34mm

Electrical

Maximum Wattage 2W (2 x 1W)

Light Characteristics

Beam Angle 10°

Colour Temperature 4000K Cool White

Lux At 1m 201

The **Double Mini Cube LED Wall Light** features a double (MCO20) spot lens creating an incredible light effect on the wall above and below it. IP65 rated allowing it to be installed in bathrooms, easy to install, low running costs and very reliable.

LED Driver Options

- LED Driver (Switching) Use this driver for on/off control. Cannot be used for dimming.
- LED Driver (Dimming) For use with nearly all domestic dimming lighting. Most resistive dimmers have a minimum load of 60W, therefore ensure that if this not met, a dummy load is added to the circuit, such as a mains voltage halogen fitting.
- LED Driver (1-10V) For use with 1-10V dimmer modules or 1-10V control systems. This type of dimming does not have a minimum load.
- Wise Chameleon (Dimming + Wireless) This controller can be used for both switching and dimming. Additionally, this unit can communicate via radio and external push buttons, allowing you to wirelessly control your fitting. Note that an additional 24V LED driver is required to power the Wise Chameleon pack.