



LEDDH2226 SS OUT

Stainless Steel 3000K Warm White
Quicklink: Q2BC0

General

Colour	Stainless Steel
Construction	Stainless Steel
Dimmable	Yes
IP Rating	IP65

Dimensions

Cut Out	91 x 91mm (Length x Width)
Depth	44mm
Height	100mm
Width	100mm

Electrical

Amperage	700mA
Maximum Wattage	3W

Light Characteristics

Colour Temperature	3000K Warm White
--------------------	------------------

The LED Aqua Low Level Outdoor is a low level light fitting that is rated IP65, making it suitable for use in bathrooms and outdoors. The fitting houses a 3W 700mA LED which can be used to light indoor walkways, stairs and corridors. The LEDDH2226 comes complete with a back box for mounting in masonry or plaster walls.

Many different LED power supplies are available that allow you to achieve more with your lighting. Simply select the correct wattage depending on how many total LED fittings it will be connected to.

LED Driver Options

- LED Driver (Switching) - Use this driver for on/off control. Cannot be used for dimming.
- LED Driver (Dimming) - For use with nearly all domestic dimming lighting. Most resistive dimmers have a minimum load of 60W, therefore ensure that if this not met, a dummy load is added to the circuit, such as a mains voltage halogen fitting.
- LED Driver (1-10V) - For use with 1-10V dimmer modules or 1-10V control systems. This type of dimming does not have a minimum load.
- Wise Chameleon (Dimming + Wireless) - This controller can be used for both switching and dimming. Additionally, this unit can communicate via radio and external push buttons, allowing you to wirelessly control your fitting. Note that an additional 24V LED driver is required to power the Wise Chameleon pack.
- DMX (Dimming + Channel Control) - This transformer can be used for both switching and dimming as well as being fully addressable and compatible with the DMX control standard.

Please note: This fitting can be installed outside. It is recommended that this fitting is not installed near the coast.

