

LED BUBBLE1SQWBL

Blue 120° Quicklink: Q2E39

General

Colour White
Construction Plastic
Dimmable Yes
IP Rating IP40
Weight 10g

Dimmable Yes

Dimensions

Bezel Depth 2.3mm

Cut Out 25mm (Diameter)

Depth 10.3mm Length 32mm Width 32mm

Electrical

Amperage 350mA Maximum Wattage 1W

Light Characteristics

Beam Angle 120°

The **Bubble Square LED** is a versatile unit. It can be used separately or together with a light fitting. It incorporates a high power 1 watt LED and hs a 25mm cut out. It is available in four different bezel colours and four different LED colours; amber, blue, cool white and warm white. These have a lumen output of 65, 27, 90 and 70lm respectively.

The lens produces an 120° angle of light. These are ideal for lighting stairs and small areas that require low power usage and a large dispersal of light.

Many different LED power supplies are available that allow you to achieve more with your lighting. Simply select the correct wattage depending on how many total LED fittings it will be connected to.

LED Driver Options

- Switching Use this driver for on/off control. Cannot be used for dimming.
- Dimming Normal Use this driver for dimming control. Some dimmers may require a resistive dummy load to meet the minimum load requirements.
- Dimming 1-10V Use this driver with a 1-10V dimmer modules or control systems. This type of dimming does not have a minimum load.