



## **LAMP 7021B RGB**

Black RGB Quicklink: Q2F32

General

Colour Black Construction Steel Dimmable Yes **IP Rating IP20** 

Dimmable Yes

**Dimensions** 

120mm (Diameter) Cut Out Diameter 135mm Minimum Ceiling 60mm

Depth

Electrical

Amperage 350mA Maximum Wattage 15W

The Spider Module is a LED module that is energy saving and conforms to Part L regulations. The fitting has 15 1W LEDs making it equivalent to a 139W mains lamp or 60W low voltage lamp.

Many different LED power supplies are available that allow you to achieve more with your lighting. Simply select the correct wattage depending on how many total LED fittings it will be connected to.

## **LED Driver Options**

- LED Driver (Switching) Use this driver for on/off control. Cannot be used for dimming.
- LED Driver (Dimming) For use with nearly all domestic dimming lighting. Most resistive dimmers have a minimum load of 60W, therefore ensure that if this not met, a dummy load is added to the circuit, such as a mains voltage halogen fitting.
- LED Driver (1-10V) For use with 1-10V dimmer modules or 1-10V control systems. This type of dimming does not have a minimum load.
- Wise Chameleon (Dimming + Wireless) This controller can be used for both switching and dimming. Additionally, this unit can communicate via radio and external push buttons, allowing you to wirelessly control your fitting. Note that an additional 24V LED driver is required to power the Wise Chameleon pack.
- DMX (Dimming + Channel Control) This transformer can be used for both switching and dimming as well as being fully addressable and compatible with the DMX control standard.