



DH2063RGB CHR

4W Chrome/Clear Quicklink: Q3020

General

Colour Chrome

Die-Cast Aluminium Construction

Controller Input 24V Controller Output 350mA **Driver Input** 240V Driver Output 24V

Dimensions

Cut Out 72mm (Diameter)

Diameter 85mm Minimum Ceiling

Depth

100mm

Electrical

Amperage 350mA Maximum Wattage 4W

The Shower Light RGB is a IP55 rated fixed downlight with a plug and play 46° RGB LED

A Chameleon Master 350mA 21W pack can operate a maximum of five 4W downlights. If more downlights are required a Chameleon Slave pack can be added which can also control a maximum of five 4W downlights. An unlimited number of 21W Chameleon Slave 350mA 21W packs can be used with a Chameleon Master 350mA 21W pack.

Wireless Switches and Remotes

A 7 button wireless wall switch or remote is needed to control the LEDs. Using either the wall switch or remote allows the user to:

- Select one of the 8 preset colours (Red, Green, Blue, Orange, Cyan, Magenta, Yellow)
- Start a smooth colour cycle
- Reverse the colour cycle
- Choose between 3 different colour cycle speeds
- Pause on one of the 1000 different shades of colours available
- Re-program the 8 preset colours with 8 colours of your own choice