

RNR4 SLA4 RGB

16W Nickel Quicklink: Q305B

General

Colour Construction IP Rating	Nickel Die-Cast Aluminium IP20
Controller Input Controller Output Driver Input Driver Output	24V 350mA 240V 24V
Dimensions Cut Out Diameter Horizontal Rotation	
Minimum Ceiling Depth Vertical Rotation	85mm 35°
Electrical Amperage	350mA

Maximum Wattage 16W (4 x 4W)

The Rock 'n' Roll 50 RGB Slave 4 Kit is used in conjunction with the Rock 'n' Roll 50 RGB Master Kits.

A Chameleon Master 350mA 21W pack can operate a maximum of five 4W downlights. If more downlights are required a Chameleon Slave pack can be added which can also control a maximum of five 4W downlights. An unlimited number of 21W Chameleon Slave 350mA 21W packs can be used with a Chameleon Master 350mA 21W pack.

Wireless Switches and Remotes

A 7 button wireless wall switch or remote is needed to control the LEDs. Using either the wall switch or remote allows the user to:

- Select one of the 8 preset colours (Red, Green, Blue, Orange, Cyan, Magenta, Yellow
- Start a smooth colour cycle
- Reverse the colour cycle
- Choose between 3 different colour cycle speeds
- Pause on one of the 1000 different shades of colours available
- Re-program the 8 preset colours with 8 colours of your own choice