



MASHIKO EM 0891 PC

Polished Chrome 28W
Quicklink: Q30B7

General

Cap	GR10q
Colour	Chrome
Construction	Steel / Glass
Dimmable	No
IP Rating	IP44

Emergency Type Maintained

Dimensions

Depth	400mm
Height	87mm
Width	400mm

Electrical

Input Voltage	240V
Maximum Wattage	28W

The **Mashiko Ceiling 400 Emergency** provides a bright diffused light through five frosted glass windows held together by a steel decorative frame. A 28W fluorescent lamp is incorporated into the fitting, meeting the requirements of Part L building regulations on the conservation of power. Additionally, this product has been converted from the original *Mashiko Ceiling 400* using a specialist pack for emergency operation.

Emergency packs are used in commercial buildings as a safety precaution in the event of a power outage, ensuring that light fittings remain on so that people can find their way out of a building in the event of an emergency.

There are two types of emergency lighting: maintained and non-maintained. Maintained light fittings are illuminated at all times using the same lamps for both normal and emergency operation, whilst non-maintained light fittings only become illuminated in the event of a power failure. This product is a maintained emergency fitting. Please note maintained emergency fittings can also be wired as non-maintained.

This fitting is IP44 rated, allowing for location in bathroom zone 2 (see technical tab). Constructed from steel and glass and finished in polished chrome. A 28W GR10q 4-Pin compact fluorescent lamp must be purchased separately.

