

Architectural LED
LED Recessed Uplight 45° 240V
3000K Warm White 16W

The **Architectural LED Recessed Uplight** is a recessed uplight that can be driven over and used in commercial or domestic applications.

The Architectural Uplight is rated IP65, this allows it to be fitted into wet areas, for example outside in decking. The body of this fitting is made of high-pure die cast aluminium ZL102; the surface is finished with electrostatic powder coating, thermostatic hardening.

A LED driver is built into the fitting, simply wire to mains supply.



HLE06301 45D W/W

3000K Warm White 16W

| | |
|-----------------------|------------------|
| General | |
| Colour | Stainless Steel |
| Construction | Aluminium |
| Dimmable | No |
| IP Rating | IP65 |
| | |
| Dimmable | No |
| Drive-Over Limits | 20,000N |
| LED Type | Cree XP |
| Number of LED's | 9 |
| Operating Temperature | -20°C ~ +60°C |
| | |
| Dimensions | |
| Cable Length | 3m |
| Cut Out | 155mm (Diameter) |
| Depth | 248mm |
| Diameter | 160mm |
| | |
| Electrical | |
| Maximum Wattage | 16W |
| Requires Driver | No |
| | |
| Light Characteristics | |
| Beam Angle | 45° |
| Colour Temperature | 3000K Warm White |
| Lumens | 1100 lm |
| Lumens Per Watt | 69 lm/W |