



LEDLINA 900 WARM

15W 3000K Warm White
Quicklink: Q32BB

General

Colour	Aluminium
Construction	Aluminium
Dimmable	Yes

Dimmable	Yes
Fitting IP Rating	IP65
Number of LED's	15
Operating Temperature	-20°C ~ +60°C

Dimensions

Cable Length	355mm
Depth	80mm
Length	900mm
Width	52mm

Electrical

Maximum Wattage	15W
-----------------	-----

Light Characteristics

Colour Temperature	3000K Warm White
Lumens	1350 lm
Lumens Per Watt	90 lm/W

The **LED Wallwasher 900** is a super bright LED wallwasher capable of lighting large outdoor structures. Being IP65 rated the fitting is completely water and weather proof.

LED Driver Options

- **LED Driver (Switching)** - Use this driver for on/off control. Cannot be used for dimming.
- **LED Driver (Dimming)** - For use with nearly all domestic dimmers. Most resistive dimmers have a minimum load of 60W, therefore ensure that if this not met, a dummy load is added to the circuit, such as a mains voltage halogen lamp or our reload product.
- **LED Driver (1-10V)** - For use with 1-10V dimmer modules or 1-10V control systems. This type of dimming does not have a minimum load.
- **Wise Scene (Dimming + Wireless)** - This controller can be used for both switching and dimming. Additionally, this unit can communicate via radio and external push buttons, allowing you to wirelessly control your fitting. Note that an additional 24V LED driver is required to power the Wise Scene pack.

Architectural Lina

LED Wallwasher 900 24V

15W 3000K Warm White



MR. RESISTOR®
Lighting Specialist Est. 1968

