



## NEBULA WHI/40 WW

3W White

Quicklink: Q38AF

### General

Colour	White
Construction	Die-Cast Aluminium
Dimmable	Yes
IP Rating	IP55
RAL Colour Code	RAL 9003

Dimmable	Yes
LED Type	Osram

### Dimensions

Cable Length	180mm
Cut Out	36mm (Diameter)
Diameter	40mm
Minimum Ceiling Depth	33mm

### Electrical

Amperage	700mA
Maximum Wattage	3W

### Light Characteristics

Beam Angle	40°
Colour Rendering Index	80
Colour Temperature	3000K Warm White
Lumens	261 lm
Lumens Per Watt	87 lm/W

The **Nebula Single 3W** is a Warm White LED Downlight that has a life time of 30,000 hours. The Nebula is available in a variety of finishes with either a narrow or wide beam angle. The Nebula is a powerful and discreet fitting.

Many different LED power supplies are available that allow you to achieve more with your lighting. Simply select the correct wattage depending on how many total LED fittings it will be connected to.

### LED Driver Options

- **Switching** - Use this driver for on/off control. Cannot be used for dimming.
- **Dimming** - Use this driver for dimming control. Some dimmers may require a resistive dummy load to meet the minimum load requirements.
- **Dimming - 1-10V** - Use this driver with a 1-10V dimmer modules or control systems. This type of dimming does not have a minimum load.

# Nebula

Nebula Single 700mA 40° Warm White 3000K  
3W White



**MR. RESISTOR**<sup>®</sup>  
Lighting Specialist Est. 1968

