

Nebula

Nebula Single 700mA 40° Warm White 3000K
3W Black



NEBULA BLK/40 WW

3W Black

Quicklink: Q3996

General

| | |
|--------------|--------------------|
| Colour | Black |
| Construction | Die-Cast Aluminium |
| Dimmable | Yes |
| IP Rating | IP55 |

| | |
|----------|-------|
| Dimmable | Yes |
| LED Type | Osram |

Dimensions

| | |
|-----------------------|-----------------|
| Cable Length | 180mm |
| Cut Out | 36mm (Diameter) |
| Diameter | 40mm |
| Minimum Ceiling Depth | 33mm |

Electrical

| | |
|-----------------|-------|
| Amperage | 700mA |
| Maximum Wattage | 3W |

Light Characteristics

| | |
|------------------------|------------------|
| Beam Angle | 40° |
| Colour Rendering Index | 80 |
| Colour Temperature | 3000K Warm White |
| Lumens | 261 lm |
| Lumens Per Watt | 87 lm/W |

The **Nebula Single 3W** is a Warm White LED Downlight that has a life time of 30,000 hours. The Nebula is available in a variety of finishes with either a narrow or wide beam angle. The Nebula is a powerful and discreet fitting.

Many different LED power supplies are available that allow you to achieve more with your lighting. Simply select the correct wattage depending on how many total LED fittings it will be connected to.

LED Driver Options

- Switching - Use this driver for on/off control. Cannot be used for dimming.
- Dimming - Use this driver for dimming control. Some dimmers may require a resistive dummy load to meet the minimum load requirements.
- Dimming - 1-10V - Use this driver with a 1-10V dimmer modules or control systems. This type of dimming does not have a minimum load.

Nebula

Nebula Single 700mA 40° Warm White 3000K
3W Black

