# Nebula Nebula Single 700mA 40° Warm White 3000K 3W Bronze



## **NEBULA BRZ/40 WW**

3W Bronze Quicklink: Q3999

#### General

General	
Colour	Bronze
Construction	Die-Cast Aluminium
Dimmable	Yes
IP Rating	IP55
Dimmable	Yes
Billingsio	-
LED Type	Osram
Dimensions	
Cable Length	180mm
Cut Out	36mm (Diameter)
Diameter	40mm
Minimum Ceiling	33mm
Depth	
Electrical	
Dimmable LED Type <b>Dimensions</b> Cable Length Cut Out Diameter Minimum Ceiling Depth	Yes Osram 180mm 36mm (Diameter)

Amperage 700mA Maximum Wattage 3W

### **Light Characteristics**

Beam Angle40°Colour Rendering80Index3000K Warm WhiteColour Temperature3000K Warm WhiteLumens261 lmLumens Per Watt87 lm/W



The **Nebula Single 3W** is a Warm White LED Downlight that has a life time of 30,000 hours. The Nebula is available in a variety of finishes with either a narrow or wide beam angle. The Nebula is a powerful and discreet fitting.

Many different LED power supplies are available that allow you to achieve more with your lighting. Simply select the correct wattage depending on how many total LED fittings it will be connected to.

#### **LED Driver Options**

- Switching Use this driver for on/off control. Cannot be used for dimming.
- Dimming Use this driver for dimming control. Some dimmers may require a resistive dummy load to meet the minimum load requirements.
- Dimming 1-10V Use this driver with a 1-10V dimmer modules or control systems. This type of dimming does not have a minimum load.



