

# Miniature Guide LED

LED Uplight 36mm Recessed 45° 24V  
3000K Warm White 0.5W



**MR. RESISTOR**<sup>®</sup>  
Lighting Specialist Est. 1968



## GL018 WARM WHITE

3000K Warm White 0.5W  
Quicklink: Q39A0

This mini (36mm diameter) path marker/ground light is ideal for both domestic and public applications. A modern waterproof design makes this unit a must for decking areas, lobby's and walkways. Combined with exceptionally low power consumption, means this product is cost effective not only to buy, but also to run.

### General

Colour Silver,Stainless Steel  
Dimmable Yes  
IP Rating IP68

### Power Supply

A 24V power supply is required for this fitting. Please use the chart below to roughly determine the correct power supply to use:

Dimmable Yes  
LED Type Luxeon

### Dimensions

Cut Out 27mm (Diameter)  
Depth 37mm  
Diameter 36mm

1 - 16 unit = DC1024VLS  
17 - 36 units = DC21024V  
37 - 46 units = RS2524  
47 - 90 units = RS5024  
91 - 180 units = RS10024

### Electrical

Maximum Wattage 0.5W

If you require more than the maximum amount of fittings listed above, you will have to use extra power supplies.

### Light Characteristics

Beam Angle 45°  
Colour Temperature 3000K Warm White

### Other things to remember.

This fitting needs to be wired in Parallel.

If using this fitting is an area which is likely to get wet, such as outdoors, bathrooms, and saunas. Please ensure that the driver is kept in a waterproof enclosure.

Please note the fitting is submersible up to a distance of 2m.

3m HO5RN-F rubber cable attached

Caution: Voltage drop can occur over long distances. Recommended minimum cable size 0.75mm<sup>2</sup>