

Trapeze

Wire Pendant Opal 12V
Nickel 20W



MR113+GLASS NKL

Nickel 20W
Quicklink: Q5D5

General

Cap	G4
Colour	Nickel
Construction	Steel / Glass
Dimmable	Yes
IP Rating	IP00

Dimensions

Diameter	118mm
Height	570mm

Electrical

Maximum Wattage	20W
Voltage	12V

The **Wire Pendant Opal** is a fixed 570mm stainless steel pendant fitting with an opal glass head.

This product must be purchased with the following *Trapeze Accessories*; *PVC Coated Wire Cable*, *Wire Tensioners* and a *Wire Transformer*. Other accessories are also available depending on the track layout you desire. For ideas and required components, please see pages 6 and 7 of our *Trapeze System Catalogue* located in the downloads tab and the *Trapeze Accessories* section.

The distance between the two lengths is 90mm.

The *Trapeze Wire System* can be run to a maximum length of 6 metres with a maximum wattage of 300W. When connecting this fitting on the cable it is important that the PVC outer casing is pierced in order to make a solid connection.

A solid core cable must be used to connect power from the *Wire Transformer* to the *Wire Tensioner*, the *PVC Coated Wire Cable* must not be used for this purpose. Alternatively, as long as the single strands of the transformer cable are bundled together tightly into one piece and soldered if possible, it can be connected to the *PVC Coated Wire Cable* via a *Wire Floating Live End* or more directly via the *Wire Tensioner*.

For further detail on connecting all cables to the *Wire Tensioners*, please see the technical tab.

Please Note: If using the LED Reality MR16 lamps, a Dim drive will be required. This will allow the lamps to dim. If using halogen lamps an MT420 transformer will be required.

Trapeze

Wire Pendant Opal 12V
Nickel 20W

