





## **LEDBUBBLE2 WH/BL**

Blue White Quicklink: Q3C0B

General

Colour White
Construction Metal
Dimmable Yes
IP Rating IP44
RAL Colour Code RAL 9010

Dimmable Yes

**Dimensions** 

Cut Out 22mm (Diameter)
Depth 14mm

29<sub>mm</sub>

Diameter **Electrical** 

Amperage 350mA Maximum Wattage 1W

**Light Characteristics** 

Beam Angle 45°

The **Bubble LED 2** is a versatile unit, ideal for lighting skirting boards, plinths, cabinets and stairs and kitchen areas.

It has a high power 1 watt LED.

The cut out is 26mm when using either of the two fixing clips. It can be glued in with a cut out of 22mm.

Two fixing clips included for 25mm or 50mm plasterboard - see installation instructions below for further information.

This fitting needs to be wired in series - see wiring diagram below.

This LED is available in a stainless steel, white metal or chrome finish bezel that has a lens that produces a 45° angle of light.

Many different LED power supplies are available that allow you to achieve more with your lighting. Simply select the correct wattage depending on how many total LED fittings it will be connected to.

## **Technical**

## **LED Driver Options**

- Switching Use this driver for on/off control. Cannot be used for dimming.
- Dimming Normal Use this driver for dimming control. Some dimmers may require a resistive dummy load to meet the minimum load requirements.
- Dimming 1-10V Use this driver with a 1-10V dimmer modules or control systems. This type of dimming does not have a minimum load.





