

LED Strip Flexible Tape Tunable White 19.2W 24V

LED Strip Flexible Tape Tunable White 5m (120xSMD 3528 LEDs/m) 24V

96W (19.2W/m) 2500K - 6500K



TAPEDYN500 24V

96W (19.2W/m) 2500K - 6500K

Quicklink: Q4057

General

Construction	Plastic
IP Rating	IP20

LED Chip	SMD 3528
LED per Tape	600

Dimensions

Cut Length	100mm
Height	4.6mm
Length	5m
Width	10mm

Electrical

Maximum Wattage	96W (5 x 19.2W)
Voltage	24V

Light Characteristics

Beam Angle	120°
Colour Rendering Index	90
Lumens	7750 lm
Lumens Per Metre	1550 lm/m
Lumens Per Watt	81 lm/W
Watts Per Metre	19.2 W/m

LED Strip Flexible Tape is a versatile light source with a wide range of uses that can be either decorative or functional. Easy to install with pre-fitted double-sided backing tape and can be cut to a specific length.

Anything from a short linear run of light for under cabinet or plinth lighting, shelving or back lighting mirrors to large scale applications such as low level lighting in corridors, dropped ceilings, cove lighting, doorways, handrails and staircases can be achieved. A wide range of extrusions and diffusers are available to suit any location and produce different effects. For example a continuous, seamless line of light can be created when mounted in Maxi extrusions combined with Liger diffusers.

LED Tunable White allows continuous colour temperature adjustment to suit a particular environment, task or mood. LED Tape Dynamic White is Colour Temperature Tunable from 2500k - 6500k over 5 metres. LED Tape Dynamic White carries an IP20 rating. A total of 7750lm (1,550lm/m - 850lm/m at 6500K and 700lm/m at 2500k)

The 1 metre LED tape is joined together via pins with a maximum of 10 metres of tape on a power cord. Multiple power cords can be connected to one driver. This LED tape can be cut every 165mm. The maximum distance between the power supply and LED tape is 20 metres. We recommend using 1.5mm² cable.

The maximum total length is 20 metres for the LED tape and power supply combined.

This LED tape is dimmable and we recommend using the Triac LED Dimming Driver. Ensure the dimming driver you use exceeds the total wattage of the LED Tape.