

# Pro Reality LED PAR30

Pro Reality LED PAR30 12W 850lm Dimmable  
35° 3000K Warm White



## PRO REALPAR3035D

35° 3000K Warm White  
Quicklink: Q40D4

### General

Cap	ES / E27
Colour	Silver
Construction	Aluminium
Dimmable	Yes

Dimmable	Yes
LED Type	Cree

### Dimensions

Diameter	95mm
Length	87mm

### Electrical

Energy Efficiency Rating	A
Maximum Wattage	12W
Voltage	240V

### Light Characteristics

Beam Angle	35°
Colour Rendering Index	93
Colour Temperature	3000K Warm White
Halogen Equivalent Wattage	100W
Lumens	850 lm
Lumens Per Watt	71 lm/W

The Pro Reality Par 30 LED is an LED lamp that matches halogen light source. This is achieved with the use of a single Cree LED chip with a reflector built around it. The result is truly warm and gives that arc of light we are all used to seeing with halogen.

We have used an improved circuit for the LED driver for smooth, flicker free dimming. We have fully tested dimming with Lutron and various dimmer modules

The Pro Reality lamps are our most powerful LED lamps yet, but with the benefit of being energy efficient, all complying to the 2013 Part L regulations. The Lamps high lumen output make them ideal for lighting large spaces and high ceilings.

The Pro Reality ranges high CRI makes it ideal for lighting residential interiors, with its superior light bringing out all the colours, materials and textures of the home. The perfect colour spectrum of the light also makes the lamps ideal for lighting artwork and ornaments.

### Key Features

- Replicates halogen reflector
- Colour Rendering Index of 93
- LED positioned further back for anti glare
- Complies with 2013 Part L regulations
- Fully dimmable with leading & trailing edge dimmers
- Equivalent to 75W Halogen
- LED Chip 15° : CREE CXA1512
- LED Chip 35° : NICHIA 757

**Please Note:** This LED lamp comes with a one year warranty as standard.



# Pro Reality LED PAR30

Pro Reality LED PAR30 12W 850lm Dimmable  
35° 3000K Warm White

---

To discover more about LED United and their products, click below.

