



LEDPANEL SM 30W CCT

Colour Temp Adjustable 2500K-7000K 30W Quicklink: Q414F

General

General	
Colour	White
Construction	Aluminium
Dimmable	Yes
Dimmable	Yes
Billingsio	-
LED Type	SMD3528
Number of LED's	384
Operating	-20°C - +40°C
Temperature	
Dimensions	
Depth	80mm
Length	600mm
Width	600mm
VVIULII	00011111
Electrical	
Maximum Wattage	30W
Voltage	24V
Light Characteristics	
Beam Angle	150°
Colour Rendering	90
Index	
Lumens	2400 lm

80 lm/W

The **LED Surfaced Panel Light Box** range features the latest in LED technology. The panels are suitable for commercial and domestic applications, included with the LED Panel is a surfaced mounting box for ceilings in which panels can't be recessed into the ceiling. These panels are ideally suited for office lighting and for meeting rooms and corridors.

This kit includes a 24V driver and a CCT adjustable touch panel controller, dimmable drivers are available as additional option.

Key Features

- Energy savings up to 70%-80% compared to fluorescent equivalent
- Instant start, no flickering or humming
- Complies with October 2010 Part L regulations
- Fully dimmable with leading edge dimmers
- Made with constant current LED tape that can work under unstable voltage.
- Compatible with RF, Dali, DMX512, 0-10V Dimmers
- No electric wave
- Excellent thermal management and refined aluminium
- Mercury free
- No RF interference
- Compatible with 2.4G controller

Lumens Per Watt