

### **LEDPANEL SM 36W RGBW**

RGBW 3000K Warm White 36W Quicklink: Q4152

#### General

Colour White
Construction Aluminium
Dimmable Yes
IP Rating IP40

Operating -20°C - +40°C

Temperature

## **Dimensions**

Depth 80mm Length 600mm Width 600mm

## Electrical

Maximum Wattage 36W Voltage 24V DC

# **Light Characteristics**

Beam Angle 120° Colour Rendering 80

Index

Colour Temperature 3000K Warm White

Lumens Per Watt 3600 lm Lumens Per Watt 100 lm/W The **LED Surfaced Panel Light Box** range features the latest in LED technology. The panels are suitable for commercial and domestic applications, included with the LED Panel is a surfaced mounting box for ceilings in which panels can't be recessed into the ceiling. These panels are ideally suited for office lighting and for meeting rooms and corridors.

The RGBW panels are colour change and white, giving the ability to choose either white or any colour or hue. This is ideal for creating different moods and ambiences in a space.

#### **Key Features**

IP40 rated

• LED type: SMD5050+SMD2835

Light emitting angle: 120°

No Flicker

LM80

• CRI80

• UGR 21

• Diffuser plate with light transmittance of 98% (1.5mm thickness)

• Different installations and applications possible