

# LED Tape Seamless 120 8W 24V

LED Tape Seamless 5m (120xSMD 3528 LEDs/m) 24V  
40W (1m=8W) 2700K Warm White



## TAPE120 5M IN

40W (1m=8W) 2700K Warm White  
Quicklink: Q4330

### General

Construction	Plastic
IP Rating	IP65

LED Chip	SMD 3528
LED per Tape	600

### Dimensions

Cut Length	50mm
Height	2.4mm
Length	5m
Width	10.5mm

### Electrical

Maximum Wattage	40W (5 x 8W)
Voltage	24V

### Light Characteristics

Beam Angle	120°
Colour Rendering Index	80
Colour Temperature	2700K Warm White
Lumens	2500 lm
Lumens Per Metre	500 lm/m
Lumens Per Watt	63 lm/W
Watts Per Metre	8 W/m

LED Tape is a versatile light source with a wide range of uses that can be either decorative or functional. Easy to install with pre-fitted double-sided backing tape and can be cut to a specific length.

Anything from a short linear run of light for under cabinet or plinth lighting, shelving or back lighting mirrors to large scale applications such as low level lighting in corridors, dropped ceilings, cove lighting, doorways, handrails and staircases can be achieved. A wide range of extrusions and diffusers are available to suit any location and produce different effects.

LED Tape Seamless carries an IP65 rating making it suitable for bathrooms and kitchens. We would recommend using this tape for indirect lighting such as the underside of cabinets or lighting shadow gaps. For direct lighting, we would recommend using our liger diffusers, with our larger channels of around 20mm internal depth to avoid dark spots.

This 5 meter LED tape can be extended to a maximum of 10 meters, when using an additional 5 meter reel and a pin connector. Please note that if you are joining 2 of the 5 meter reels together, the join between the tapes may show a dark spot depending on how it is to be installed. For certain installations, we may advise using a 10 meter reel instead.

This LED tape is dimmable and we recommend using the Triac LED Dimming Driver. Ensure the dimming driver you use exceeds the total wattage of the LED Tape.