

Kozus LED Extrusion Profile - Plaster-In Ceiling

Kozus Trimless LED Tape Extrusion Profile Plaster-in
Aluminium 2000mm



MR. RESISTOR[®]
Lighting Specialist Est. 1968



KOZUS ALU 2.0M

Aluminium 2000mm

Quicklink: Q43C2

General

| | |
|--------------|-----------|
| Colour | Aluminium |
| Construction | Aluminium |

Dimensions

| | |
|--------------------------|--------|
| Depth | 17.5mm |
| Length | 2m |
| Minimum Ceiling Depth | 17.5mm |
| Width | 66.8mm |

The Kozus profile is designed for mounting in drywall. It makes a LED fixture that creates a line of light in wall and ceiling surfaces with no aluminum parts showing.

Technical

KOZUS profile can be fixed in slots made in previously fitted drywall using gypsum adhesive (GS 20 CECOL) or mounting adhesive. Before you fix the profile in drywall, you should take care to lead the power cables out. They can be led in the profile by cutting a hole in the aluminum or end cap. After the glue dries, cover aluminum collars thinly with a suitable adhesive, put the drywall mesh on, fill all and when dry, polish it in such a way that it does not affect the base edge of the profile. Finally, apply paint over the base edge of the profile.

Make sure to cover the profile while performing the above work. When you have finished, remove the working cover, mount the LEDs, solder the power wires, and finally, put on a clean cover.

Please note: The Kozus profile is not compatible with mounting springs (KMA groove springs).

Kozus LED Extrusion Profile - Plaster-In Ceiling

Kozus Trimless LED Tape Extrusion Profile Plaster-in
Aluminium 2000mm



MR. RESISTOR[®]
Lighting Specialist Est. 1968

