



DOT/3E/WHT

3W 120°

Quicklink: Q4415

General

Colour White
Construction Aluminium

Dimmable No IP Rating IP20

Battery 3 hrs

Dimensions

Cut Out 32mm (Diameter)

Depth 26mm
Diameter 37mm
Minimum Ceiling 26mm

Depth

Electrical

Amperage 400mA Maximum Wattage 3W Voltage 240V

Light Characteristics

Beam Angle 120° Colour Rendering 80

Index

Colour Temperature 6500K Daylight

Lumens Per Watt 195 lm 65 lm/W

The DOT3 LED emergency luminaire is a complete and easy solution for 3 hour emergency down lighter applications. It is designed to be small and discreet by housing the electronic control gear together with the latest LiFePO4 batteries within a small enclosure. The result is a small plug and play emergency down lighter that fits through a 32mm aperture. The green charging indicator is easily visible whilst the unit is charging, but is completely unobtrusive due to its 1mm size.

Emergency downlights are traditionally fitted in corridors and near fire exits to allow safe evacuation of buildings in the event of a power outage.

Product Description

- Push and lock connector for easy installation
- Unobtrusive green charging indicator
- Open Area Lens & Corridor Lens versions available
- 195 lumens output / 65 lumens p/w
- Designed to BS EN60598-2-22
- High Efficiency LiDeP04 batteries
- Available in White, Black & Grey