

## **BLOB BF2815/EMERG**

25° 4000K Cool White Quicklink: Q45FB

General

Colour White
Construction Aluminium

Dimmable No

Battery 3 hrs

Emergency Type Maintained

**Dimensions** 

Cut Out 100mm (Diameter)

Diameter 122mm Minimum Ceiling 106mm

Depth


Electrical

Maximum Wattage 9W Voltage 240V

**Light Characteristics** 

Beam Angle 25°

Colour Temperature 4000K Cool White



The **Blob** is a high powered LED downlight with a silver reflector. A LED driver is wired into the fitting, simply wire to mains.

The **Blob** range of fittings are light weight simplifying installation. This fitting is not dimmable.

This kit includes the **Blob Downlight LED Emergency Pack** which is a maintained, fireproof emergency pack compatible with the Blob Downlight (switched) range.

Emergency packs are used in commercial buildings as a safety precaution during a power outage, so that people will be able to find their way out of a building in the event of an emergency.

This is a maintained emergency pack.

Maintained Emergency Lighting: The emergency light units are illuminated at all times using the same lamps for both normal and emergency operation. Please note maintained fittings can be wired as non-maintained.

**Non-Maintained Emergency Lighting:** A non-maintained fitting is not illuminated until the event of power failure.

