

**LEDHLF23401 WARM/EMERG**

90° 3000K Warm White

Quicklink: Q4601

General

Colour	White
Construction	Aluminium
Dimmable	No

Emergency Type Maintained

Dimensions

Cut Out	130mm (Diameter)
Diameter	148mm
Minimum Ceiling Depth	117mm

Electrical

Maximum Wattage	8W
Voltage	240V

Light Characteristics

Beam Angle	90°
Colour Temperature	3000K Warm White

The **Frisbee 8W** is a high powered SMD5630 8W LED downlight with a silver inner ring and transparent panel. A LED driver is incorporated into the fitting, simply wire to mains.

The **Frisbee** range of fittings are light weight simplifying installation. The transparent panel creates a soft uniform light, ideal for commercial applications. This fitting is not dimmable.

This kit includes the **Frisbee Downlight LED Emergency Pack** which is a maintained, fireproof emergency pack compatible with the Frisbee Downlight range.

Emergency packs are used in commercial buildings as a safety precaution during a power outage, so that people will be able to find their way out of a building in the event of an emergency.

This is a maintained emergency pack.

Maintained Emergency Lighting: The emergency light units are illuminated at all times using the same lamps for both normal and emergency operation. Please note maintained fittings can be wired as non-maintained.

Non-Maintained Emergency Lighting: A non-maintained fitting is not illuminated until the event of power failure.

Frisbee

Frisbee Downlight 8W 240V Emergency Kit
90° 3000K Warm White



MR. RESISTOR[®]
Lighting Specialist Est. 1968

