

## **LEDHLF23401 WARM/EMERG**

90° 3000K Warm White Quicklink: Q4601

General

Colour White Construction Aluminium

Dimmable No

Emergency Type Maintained

**Dimensions** 

Cut Out 130mm (Diameter)

Diameter 148mm Minimum Ceiling 117mm

Depth

Electrical

Maximum Wattage 8W Voltage 240V

**Light Characteristics** 

Beam Angle 90°

Colour Temperature 3000K Warm White



The **Frisbee 8W** is a high powered SMD5630 8W LED downlight with a silver inner ring and transparent panel. A LED driver is incorporated into the fitting, simply wire to mains.

The **Frisbee** range of fittings are light weight simplifying installation. The transparent panel creates a soft uniform light, ideal for commercial applications. This fitting is not dimmable.

This kit includes the **Frisbee Downlight LED Emergency Pack** which is a maintained, fireproof emergency pack compatible with the Frisbee Downlight range.

Emergency packs are used in commercial buildings as a safety precaution during a power outage, so that people will be able to find their way out of a building in the event of an emergency.

This is a maintained emergency pack.

**Maintained Emergency Lighting:** The emergency light units are illuminated at all times using the same lamps for both normal and emergency operation. Please note maintained fittings can be wired as non-maintained.

**Non-Maintained Emergency Lighting:** A non-maintained fitting is not illuminated until the event of power failure.

