



LED PANEL 30W/WW/EMERG

3000K Warm White 30W
Quicklink: Q460E

General	
Colour	White
Construction	Aluminium
Dimmable	No
IP Rating	IP54
Dimmable	No
LED Type	SMD3528
Number of LED's	322
Operating Temperature	-20°C - +40°C
Dimensions	
Depth	10mm
Length	600mm
Width	300mm
Electrical	
Amperage	1150mA
Maximum Wattage	30W
Voltage	24V
Light Characteristics	
Beam Angle	150°
Colour Rendering Index	83
Colour Temperature	3000K Warm White
Halogen Equivalent Wattage	75W
Lumens	1425 lm
Lumens Per Watt	48 lm/W

Included in this kit is the **LED Panel Emergency Pack**, which is a maintained emergency pack compatible with the majority of the LED panel range.

Please note: This is not dimmable.

Emergency packs are used in commercial buildings as a safety precaution during a power outage, so that people will be able to find their way out of a building in the event of an emergency.

Maintained Emergency Lighting: The emergency light units are illuminated at all times using the same lamps for both normal and emergency operation. Please note maintained fittings can be wired as non-maintained.

Non-Maintained Emergency Lighting: A non maintained fitting is not illuminated until the event of power failure.

The **LED Panel** range features the latest in LED technology. The panels are suitable for commercial and domestic applications, and are designed to fit directly into existing standard suspended ceilings and recesses, or can be suspended (fixings available separately). These panels are ideally suited for office lighting and for meeting rooms and corridors. Please note a 24V driver is required to power this product.

Key Features

- Energy savings up to 70%-80% compared to fluorescent equivalent
- Instant start, no flickering or humming
- Complies with October 2010 Part L regulations
- Made with constant current LED tape that can work under unstable voltage.
- No electric wave
- Excellent thermal management and refined aluminium
- Mercury free
- No RF interference