



V-PRO GJP100

Beige 100W Quicklink: Q462D

G	_	n	_	r	_	ı
U	ᆫ	H	ᆫ	ı	а	ı

Colour Beige
Construction Plastic/Metal

IP Rating IPO0

Load Type Resistive Trailing

Edge

Spindle Length 15mm

Dimensions

Depth 23mm Length 48.5mm Width 25mm

Electrical

Maximum Wattage 100W Minimum Wattage 10W Voltage 240V The LED Trailing Edge 2 Way Push-On / Off Rotary Dimmer 1-10 LEDs (1 Gang Space) is designed for use with trailing edge electronic low voltage transformers. V-Pro series comprises programmable intelligent dimmers with a choice of dimming modes for wider compatibility; some have a push-on/push-off switch action with rotary dimming and others (called V-Pro IR and V-Pro Eclique2) have touch/remote control. All V-Pro dimmers offer superior dimming technology to deliver the best possible dimming performance for a given load. Suitable for mains lighting, most dimmable electronic transformers and, with no minimum load, are suitable for dimmable low energy lighting, including many dimmable LEDs. In addition, users can set the minimum load level for the dimmer to optimise the dimming range of a particular lighting load. Controlled by a micro-processor, V-Pro dimmers offer sophisticated overload protection. Best results with low voltage lighting use VARILIGHT intelligent dimmer switches with VARILIGHT electronic transformers. V-Pro dimmers are not suitable for wire-wound "toroidal" transformers. See also: How to Program Varilight V-Pro Dimmers

Using trailing edge technology this module has many advantages over conventional (leading edge) dimmers:

- Lower power losses in the dimmer
- Virtually no electromagnetic interference
- Quiet in operation
- Soft start
- Overcurrent and short circuit shut down
- Maximum load LED: 100W up to 10 lamps
- Maximum load incandescent: 200W