

LED Tape Accessories

LED Tape Seamless Corner (6xSMD 3528 LEDs) 24V
1W 6500K Daylight



TAPE120L CNR CW

1W 6500K Daylight
Quicklink: Q4649

General

Construction Plastic
IP Rating IP65

Dimensions

Height 2.4mm
Length 38mm
Width 38mm

Electrical

Maximum Wattage 1W
Voltage 24V

Light Characteristics

Colour Temperature 6500K Daylight

LED Tape is a versatile light source with a wide range of uses that can be either decorative or functional. Easy to install with pre-fitted double-sided backing tape and can be cut to a specific length.

Anything from a short linear run of light for under cabinet or plinth lighting, shelving or back lighting mirrors to large scale applications such as low level lighting in corridors, dropped ceilings, cove lighting, doorways, handrails and staircases can be achieved. A wide range of extrusions and diffusers are available to suit any location and produce different effects. For example a continuous, seamless line of light can be created when mounted in Maxi extrusions combined with Liger diffusers.

LED Tape Seamless carries an IP65 rating making it suitable for bathrooms and kitchens.

The 1 metre LED tape is joined together via pins with a maximum of 10 metres of tape on a power cord. Multiple power cords can be connected to one driver. This LED tape can be cut every 50mm. The maximum distance between the power supply and LED tape is 20 metres. We recommend using 1.5mm² cable. The maximum total length is 20 metres for the LED tape and power supply combined.

This LED tape is dimmable and we recommend using the Triac LED Dimming Driver. Ensure the dimming driver you use exceeds the total wattage of the LED Tape.

NOTE: This is only compatible with the LED Tape Seamless 120 24V Range.
