





## FIREDLC3004

50W Black Quicklink: Q4A6F

General

Cap GU10 Colour Black

Construction Die-Cast Aluminium

Dimmable Yes IP Rating **IP00** RAL Colour Code **RAL 9004** 

**Dimensions** 

Cut Out 76mm (Diameter)

Diameter 90mm

Minimum Ceiling 85mm (Standard Depth LED), 117mm (Long

40°

LED) Vertical Rotation

Electrical


Maximum Wattage 50W Voltage 240V The Invisible Adjustable Fire Rated Camera Round is an adjustable downlight designed to blend seamlessly into its surroundings. It has an unobtrusive one millimetre plate that sits practically flush to the ceiling when fitted and contains a baffle that recesses the lamp to reduce glare. The baffle is also hinged to allow the light source to be directed through a 40 degree arc from the vertical.


Please note: the ceiling depth for this downlight depends on the lamp choice. For a standard GU10 lamp the depth is 85mm. For a LED GU10 lamp a ceiling depth of 115mm should be allowed.

The Invisible range has been designed to be overpainted in Situ in the ceiling if necessary. The fitting is painted RAL9004 - 30% Gloss level which has a slightly matt surface, to which the emulsion or other paints will adhere to. The finish from the factory is good enough for normal use and will blend in with the most common ceiling finishes. The slightly matt finish on the product will allow it to be carefully repainted to suit any other ceiling colours.





Dimensions using our GU10 LED 7W lamps





Dimensions using our LED Module





Dimensions using our GU10 LED 7W lamps

