

LED FLX Stix NDPro (Diva-3) Dimmable  
LED Linear Light FLX Stix NDPro (Diva 3) Dimmable Warm White 3000K  
24V 95mm  
1W 75 lm



**MR. RESISTOR®**  
Lighting Specialist Est. 1968



## NDP1 24V30K

1W 75 lm  
Quicklink: Q4A78

### General

|              |         |
|--------------|---------|
| Colour       | White   |
| Construction | Plastic |
| Dimmable     | Yes     |
| IP Rating    | IP20    |

|                       |            |
|-----------------------|------------|
| Dimmable              | Yes        |
| Maximum Connection    | 55W        |
| Operating Temperature | 0°C ~ 40°C |

### Dimensions

|        |      |
|--------|------|
| Length | 95mm |
|--------|------|

### Electrical

|                 |        |
|-----------------|--------|
| Maximum Wattage | 1W     |
| Voltage         | 24V DC |

### Light Characteristics

|                        |                  |
|------------------------|------------------|
| Colour Rendering Index | 90               |
| Colour Temperature     | 3000K Warm White |
| Lumens                 | 75 lm            |
| Lumens Per Metre       | 789 lm/m         |
| Lumens Per Watt        | 75 lm/W          |
| Watts Per Metre        | 10.5 W/m         |

The **LED Diva3** is a slender fixture that fits almost anywhere and is perfect for showcases and retail cabinet displays. It's a little light that packs a big punch and is easy to install with a quick connection system. The Diva can be fixed by either magnets or clips both provided with the fitting.

### Key Features

- Dark spot free at the linking point
- Eco friendly product
- Super slim size
- Various mounting method

LED FLX Stix NDPro (Diva-3) Dimmable  
LED Linear Light FLX Stix NDPro (Diva 3) Dimmable Warm White 3000K  
24V 95mm  
1W 75 lm



**MR. RESISTOR®**  
Lighting Specialist Est. 1968

| Model Number             | Voltage Input (V) | Power Input (W) | A mm   | B mm   | C mm  | D mm | E mm | F mm | G mm |
|--------------------------|-------------------|-----------------|--------|--------|-------|------|------|------|------|
| NDP14-Cob9(9-24V-C90-138 | DC24              | .5              | 33.2   | 38.3   | 55.12 | 12   | 12.6 | 10.6 | 11.5 |
| NDP14-Cob9(9-24V-C90     | DC24              | 1               | 94.7   | 99.8   | 116.9 | 12   | 12.6 | 10.6 | 11.5 |
| NDP14-Cob9(9-24V-C90     | DC24              | 3               | 186.2  | 193.3  | 210.4 | 12   | 12.6 | 10.6 | 11.5 |
| NDP14-Cob9(9-24V-C90     | DC24              | 4               | 279.2  | 284.3  | 301.4 | 12   | 12.6 | 10.6 | 11.5 |
| NDP74-Cob9(9-24V-C90     | DC24              | 7               | 558.7  | 563.8  | 580.9 | 12   | 12.6 | 10.6 | 11.5 |
| NDP11-Cob9(9-24V-C90     | DC24              | 11              | 837.7  | 842.8  | 859.9 | 12   | 12.6 | 10.6 | 11.5 |
| NDP15-Cob9(9-24V-C90     | DC24              | 15              | 1116.8 | 1121.9 | 1139  | 12   | 12.6 | 10.6 | 11.5 |

