

# LED FLX Stix NDPro (Diva-3) Dimmable

LED Linear Light FLX Stix NDPro (Diva 3) Dimmable Warm White 3000K 24V 838mm  
11W 825 lm



## NDP11 24V30K

11W 825 lm  
Quicklink: Q4A7C

### General

|                       |            |
|-----------------------|------------|
| Colour                | White      |
| Construction          | Plastic    |
| Dimmable              | Yes        |
| IP Rating             | IP20       |
| Dimmable              | Yes        |
| Maximum Connection    | 55W        |
| Operating Temperature | 0°C ~ 40°C |

### Dimensions

|        |       |
|--------|-------|
| Length | 838mm |
|--------|-------|

### Electrical

|                 |        |
|-----------------|--------|
| Maximum Wattage | 11W    |
| Voltage         | 24V DC |

### Light Characteristics

|                        |                  |
|------------------------|------------------|
| Colour Rendering Index | 90               |
| Colour Temperature     | 3000K Warm White |
| Lumens                 | 825 lm           |
| Lumens Per Metre       | 984 lm/m         |
| Lumens Per Watt        | 75 lm/W          |
| Watts Per Metre        | 13.1 W/m         |

The LED Diva3 is a slender fixture that fits almost anywhere and is perfect for showcases and retail cabinet displays. It's a little light that packs a big punch and is easy to install with a quick connection system. The Diva can be fixed by either magnets or clips both provided with the fitting.

### Key Features

- Dark spot free at the linking point
- Eco friendly product
- Super slim size
- Various mounting method

LED FLX Stix NDPro (Diva-3) Dimmable

LED Linear Light FLX Stix NDPro (Diva 3) Dimmable Warm White 3000K 24V 838mm

11W 825 lm

| Model Number           | Voltage Input (V) | Power Input (W) | A mm   | B mm   | C mm  | D mm | E mm | F mm | G mm |
|------------------------|-------------------|-----------------|--------|--------|-------|------|------|------|------|
| NDP1-Cob9(6-24V-C90    | DC24              | .5              | 33.2   | 38.3   | 55.12 | 12   | 12.6 | 10.6 | 11.5 |
| NDP1-H-Cob9(6-24V-C90  | DC24              | 1               | 94.7   | 99.8   | 116.9 | 12   | 12.6 | 10.6 | 11.5 |
| NDP3-H-Cob9(6-24V-C90  | DC24              | 3               | 186.2  | 193.3  | 210.4 | 12   | 12.6 | 10.6 | 11.5 |
| NDP4-H-Cob9(6-24V-C90  | DC24              | 4               | 279.2  | 284.3  | 301.4 | 12   | 12.6 | 10.6 | 11.5 |
| NDP7-H-Cob9(6-24V-C90  | DC24              | 7               | 558.7  | 563.8  | 580.9 | 12   | 12.6 | 10.6 | 11.5 |
| NDP11-H-Cob9(6-24V-C90 | DC24              | 11              | 837.7  | 842.8  | 859.9 | 12   | 12.6 | 10.6 | 11.5 |
| NDP15-H-Cob9(6-24V-C90 | DC24              | 15              | 1116.8 | 1121.9 | 1139  | 12   | 12.6 | 10.6 | 11.5 |

