



## **RL7317/LED**

Black 20W Quicklink: Q53F0

General

Colour Black
Construction Plastic

**Dimensions** 

Height 30mm Length 110mm Width 60mm

Electrical

Maximum Wattage 20W Minimum Wattage 20W Voltage 24V DC The **24V/350mA-700mA LED Floor or Table light dimmer** has an electronic transformer incorporated. It has a 240V mains input and a selectable output. 350mA = 15W

400mA = 17W

450mA = 19W

500mA = 20W

550mA = 20W

600mA = 20W

650mA = 20W

700mA = 20W

## 24V = 20WGeneral Characteristics

- Amperometric protection
- Protection against transitory surge voltages
- Self-resetting protection against short circuit and overload
- Soft-Start mechanism
- Radio frequency interference fitter conforming to EN55015 AM1Installation Instruction Use electronic converter exclusively with resistive loads and class 2 and 3 lighting appliancesObserve plate values shownPlace electronic converter away from heat sourcesTighten terminal screw accuratelyMaximum length of connecting cable not more than 2mRemove upper plastic coverCable model. use cable type H03VV-F or H03VV-H2F. Block cable with cable clampsPush spindle of potentiometer to limit stop, replace upper plastic cover after having pushed slider also to limit stopClose plastic cover with screws