



LED BUBBLE3 WHT

3000K Warm White 45°
Quicklink: Q9AD

General

Colour White
Dimmable Yes
IP Rating IP00

Dimmable Yes

Dimensions

Cut Out 50mm (Diameter)
Diameter 56mm

Electrical

Amperage 350mA

Light Characteristics

Beam Angle 45°
Colour Temperature 3000K Warm White

The **Bubble LED Triple** is a versatile unit. It can be used separately or together with a light fitting. It has a 50mm cut out. It has three high power 1 watt LEDs.

This LED has a white surround which has three lens that produce a 45° angle of light.

Many different LED power supplies are available that allow you to achieve more with your lighting. Simply select the correct wattage depending on how many total LED fittings it will be connected to.

LED Driver Options

- LED Driver (Switching) - Use this driver for on/off control. Cannot be used for dimming.
- LED Driver (Dimming) - For use with nearly all domestic dimming lighting. Most resistive dimmers have a minimum load of 60W, therefore ensure that if this not met, a dummy load is added to the circuit, such as a mains voltage halogen fitting.
- LED Driver (1-10V) - For use with 1-10V dimmer modules or 1-10V control systems. This type of dimming does not have a minimum load.
- Wise Chameleon (Dimming + Wireless) - This controller can be used for both switching and dimming. Additionally, this unit can communicate via radio and external push buttons, allowing you to wirelessly control your fitting. Note that an additional 24V LED driver is required to power the Wise Chameleon pack.