

## TAPEDD60 5M WW

145W (29W/m) 3000K Warm White
Quicklink: Q6932

### General

| | |
|---|---|
| Dimmable | Yes |
| IP Rating | IP20 |

### Dimensions

| | |
|---|---|
| Cut Length | 95mm |
| Height | 2mm |
| Length | 5m |
| Width | 20mm |

### Electrical

| | |
|---|---|
| Maximum Wattage | 145W (5 x 29W) |
| Voltage | 24V DC |

### Light Characteristics

| | |
|---|---|
| Beam Angle | 120° |
| Colour Rendering Index | 90+ |
| Colour Temperature | 3000K Warm White |
| Lumens | 10500 lm |
| Lumens Per Metre | 2100 lm/m |
| Lumens Per Watt | 72 lm/W |
| Watts Per Metre | 29 W/m |

Enhance your lighting with our Double Row LED Strip Light Flexible Tape. Featuring a 20mm width and a larger emission surface, this strip offers superior lighting effect. Ideal for professional installations, it boasts increased brightness with more LEDs spread out per metre, delivering approx. 2300 lm/m per metre and offering CRI rating greater than 90. Perfect for applications where high-quality, bright lighting is essential.


Flexible LED Strip Light Tape is a versatile light source with a wide range of uses that can be either decorative or functional. Easy to install with pre-fitted 3M 300LSE double-sided tape and can be cut to a specific length.

Anything from a short linear run of light for under cabinet or plinth lighting, shelving or back lighting mirrors to large scale applications such as low level lighting in corridors, dropped ceilings, cove lighting, doorways, handrails and staircases can be achieved. A wide range of extrusions and diffusers are available to suit any location and produce different effects.

This extremely bright LED strip light is ideal for architectural decorative and commercial setting due to its brightness and double line of LEDs. It can be cut every 6LEDs (95mm approx,) and there are 16mm centre to centre between LEDs.



t: +44 (0)20 8874 2234 e: info@mr-resistor.co.uk **www.mr-resistor.co.uk**






t: +44 (0)20 8874 2234 e: info@mr-resistor.co.uk www.mr-resistor.co.uk