

LED Bubble 2 Skirting Lights

LED Bubble 2 Skirting Light 1W 350mA
Warm White 2700K White



LEDBUBBLE2 WH/IN

Warm White 2700K White
Quicklink: Q6959

General

Colour	White
Construction	Metal
Dimmable	Yes
IP Rating	IP44
RAL Colour Code	RAL 9010

Dimensions

Cut Out	22mm (Diameter)
Depth	14mm
Diameter	29mm

Electrical

Amperage	350mA
Maximum Wattage	1W

Light Characteristics

Beam Angle	45°
Colour Temperature	2700K Warm White

The **Bubble LED 2** is a versatile unit, ideal for lighting skirting boards, plinths, cabinets and stairs and kitchen areas.

It has a high power 1 watt LED.

The cut out is 26mm when using either of the two fixing clips. It can be glued in with a cut out of 22mm.

Two fixing clips included for 25mm or 50mm plasterboard - see installation instructions below for further information.

This fitting needs to be wired in series - see wiring diagram below.

This LED is available in a stainless steel, white metal or chrome finish bezel that has a lens that produces a 45° angle of light.

Many different LED power supplies are available that allow you to achieve more with your lighting. Simply select the correct wattage depending on how many total LED fittings it will be connected to.

Technical

LED Driver Options

- Switching - Use this driver for on/off control. Cannot be used for dimming.
- Dimming - Normal - Use this driver for dimming control. Some dimmers may require a resistive dummy load to meet the minimum load requirements.
- Dimming - 1-10V - Use this driver with a 1-10V dimmer modules or control systems. This type of dimming does not have a minimum load.

LED Bubble 2 Skirting Lights

LED Bubble 2 Skirting Light 1W 350mA

Warm White 2700K White

