

# Tornado Evo

Tornado EVO Batten CCT Selectable (4K/5K/65K)  
1200mm 20-40W



**MR. RESISTOR®**  
Lighting Specialist Est. 1968



## ATORE4/1

1200mm 20-40W  
Quicklink: Q6D2F

### General

Colour	Grey
IP Rating	IP65
Weight	1.46kg

### Dimensions

Height	80mm
Length	1200mm
Width	96mm

### Electrical

Maximum Wattage	40W
Voltage	240V

### Light Characteristics

Beam Angle	120°
Colour Rendering Index	80
Lumens	6100 lm
Lumens Per Watt	153 lm/W

Tornado EVO Batten Light IP65 rating and non-corrosive with high efficiency up to 160 Lm/W. CCT selectable between 4000K, 5000K and 6500K and power selectable; offering a choice of 2 outputs, in one luminaire. Slim sloped diffuser design creates sleek appearance and offers greater light distribution - 3000lm - 6100lm (4000K) / 150lm/W (4000K)

### Key Features

- IP65 non-corrosive batten suitable for industrial applications and ancillary areas
- High efficiency up to 160 Lm/W
- CCT selectable between 4000K, 5000K and 6500K and power selectable; offering a choice of 2 outputs, in one luminaire
- Slim sloped diffuser design creates sleek appearance and offers greater light distribution
- LED performance allows point-to-point replacement of existing fluorescent luminaires
- Lockable heavy-duty stainless steel clips supplied as standard for added safety and security
- Whole luminaire illuminates during emergency operation rather than a small area, allowing less emergency versions required on an installation

## Product Video

# Tornado Evo

Tornado EVO Batten CCT Selectable (4K/5K/65K)  
1200mm 20-40W



**MR. RESISTOR®**  
Lighting Specialist Est. 1968

