

Lightspan+ Pus LED Batten

Lightspan+ Pro LED 1470mm (5ft) Twin Power and CCT Adjustable T8

Batten Surface Mounted Only

White 30/35/42/52W - CCT 3000/4000/6500K



MR. RESISTOR®
Lighting Specialist Est. 1968



ILBTC170

White 30/35/42/52W - CCT

3000/4000/6500K

Quicklink: Q6D57

General

Colour	White
Construction	Steel
Dimmable	No
IP Rating	IP20
Weight	2.1kg

Dimensions

Height	71mm
Length	1470mm
Width	60mm

Electrical

Energy Efficiency Rating	D
Maximum Wattage	52W
Minimum Wattage	30W
Voltage	240V

Light Characteristics

Beam Angle	120°
Lumens	7540 lm
Lumens Per Watt	145 lm/W

The Lightspan+ Pro T8 Batten 5ft is a premium LED solution for commercial, industrial, and residential lighting. Featuring adjustable power settings (30W–52W) and three selectable colour temperatures (3000K, 4000K, 6500K), it delivers up to 7540 lumens with an outstanding 145lm/W efficiency. Designed for flexibility and performance, this linkable, non-dimmable batten offers a 120° beam angle, IK08 impact resistance, and IP20 rating, making it ideal for high-demand indoor environments.

Key Technical Specifications:

- Power Settings: 30W / 35W / 42W / 52W
- Lumen Output: 4050-7540LM (depending on setting)
- Selectable 30W: 4050/4500/4050lm 35W: 4550/5080/4550lm 42W: 5460/6090/5460 52W: 6760/7540/6760lm
- Colour Temperatures: 3000K / 4000K / 6500K
- Efficacy: Up to 145lm/W
- Size 5ft (1470mm)
- Beam Angle: 120°
- CRI: 80
- Lifetime: 50,000 hours
- Switching Cycles: 25,000
- Mounting: Ceiling-mounted, linkable
- Material: Steel & polycarbonate
- IP Rating: IP20
- IK Rating: IK08