

Pixo Zoom Lens Track Lights

Pixo Zoom Lens 17° - 60° Selectable CCT Three Circuit Track Light 2100lm
White 12W, 18W, 25W



PIXOZ 0004520

White 12W, 18W, 25W
Quicklink: Q6D8A

General

Colour	White
Construction	Aluminium
Dimmable	No
IP Rating	IP20
Weight	940g

Dimensions

Diameter	85mm
Length	170mm

Electrical

Amperage	600mA
Maximum Wattage	25W
Minimum Wattage	12W

Light Characteristics

Beam Angle	17,60°
Colour Rendering Index	90
Lumens	2100 lm
Lumens Per Watt	84 lm/W

The PIXO ZOOM 2100LM is a versatile LED track spotlight designed for commercial and professional environments such as retail spaces, galleries, museums, and offices. Its compact design integrates advanced lighting features, offering flexibility in beam angle, power output, and colour temperature.

This model includes a zoomable beam angle ranging from 17° to 60°, allowing precise control over light distribution. The 3CCT switchable colour temperatures (2700K, 3000K, 4000K) provide adaptable ambiance for different settings. The Multipower driver enables selectable wattage (12W, 18W, 25W) directly from the track adaptor, simplifying installation and energy management.

Key Features

- Beam Angle Adjustment: Zoomable from 17° to 60° for targeted or wide illumination
- 3CCT Colour Temperature: Selectable between 2700K, 3000K, and 4000K
- Multipower Driver: Choose between 12W (300mA), 18W (450mA), 25W (600mA Max) output via track adaptor
- High Efficiency: Up to 2100 lumens with 84 lm/W efficacy
- Low Flicker: Flicker rate below 5% for visual comfort
- Durable Construction: Die-cast aluminium body with textured finish
- Flexible Positioning: 345° rotation and 90° tilt for directional lighting
- Long Lifespan: Rated up to 100,000 hours

Pixo Zoom Lens Track Lights

Pixo Zoom Lens 17° - 60° Selectable CCT Three Circuit Track Light 2100lm
White 12W, 18W, 25W

