

HR-Slim LED Extrusion Profile - Floor

HR-Slim LED Floor and Wall Extrusion Profile

Anodised Aluminium 2000mm



MR. RESISTOR®
Lighting Specialist Est. 1968



HR-SLIM 2M

Anodised Aluminium 2000mm

Quicklink: Q6DB8

General

Colour	Aluminium
Construction	Anodised Aluminium

Dimensions

Height	10mm
Length	2m
Width	18.8mm

Create a stunning continuous line of light that flows effortlessly from floor to wall and across the ceiling — all without visible diodes. This innovative LED profile delivers uniform illumination, adding a modern architectural touch to any interior.

Perfect for residential settings such as dining rooms, bedrooms, living rooms, and bathrooms, it allows you to enhance your space with a sophisticated, ambient glow.

Designed for use with ceramic tiles, terracotta, and quartz sinters, the profile is built to last. Once the cover is pressed into place from above, the surface becomes walkable, scratch-resistant, and crack-resistant, ensuring both style and durability.

Please note: for IP67 rating, profile requires sealing with silicone.

Key Features

- Seamless light transition – enables smooth illumination from floor to wall to ceiling with no visible diodes.
- Uniform brightness – consistent light output without dimming at corners or profile joins.
- Highly durable – walkable surface resistant to scratches, cracks, and high pressure.
- Heavy-duty performance – withstands loads up to 500 kg (IK08 rating).
- Versatile design – compatible with ceramic tiles, terracotta, and quartz sinters.
- Creative freedom – allows the formation of circles and arcs on floors, walls, and ceilings.
- Easy installation – dedicated click-in cover enables quick assembly and IP65 sealing.
- Enhanced protection – achieve IP67 sealing with silicone for maximum moisture resistance.