

LED FLX Stix NDPro (Diva-3) Dimmable

LED FLX Stix NDPro (Diva 3) Sidefeed Warm White 3000K 24V 188mm

3W 225 lm



NDP3 24V30K-S

3W 225 lm

Quicklink: Q6E25

General

|                       |            |
|-----------------------|------------|
| Colour                | White      |
| Construction          | Plastic    |
| Dimmable              | Yes        |
| IP Rating             | IP20       |
|                       |            |
| Dimmable              | Yes        |
| Maximum Connection    | 55W        |
| Operating Temperature | 0°C ~ 40°C |

Dimensions

|        |       |
|--------|-------|
| Length | 188mm |
|--------|-------|

Electrical

|                 |        |
|-----------------|--------|
| Maximum Wattage | 3W     |
| Voltage         | 24V DC |

Light Characteristics

|                        |                  |
|------------------------|------------------|
| Colour Rendering Index | 90               |
| Colour Temperature     | 3000K Warm White |
| Lumens                 | 225 lm           |
| Lumens Per Metre       | 1197 lm/m        |
| Lumens Per Watt        | 75 lm/W          |
| Watts Per Metre        | 16 W/m           |

The **LED Diva3** is a slender fixture that fits almost anywhere and is perfect for showcases and retail cabinet displays. It's a little light that packs a big punch and is easy to install with a quick connection system. The Diva can be fixed by either magnets or clips both provided with the fitting. Sidefeed for seamless extension. Powered only through cable, no power supply on the input connector

Key Features

- Dark spot free at the linking point
- Eco friendly product
- Super slim size
- Various mounting method

# LED FLX Stix NDPro (Diva-3) Dimmable

LED FLX Stix NDPro (Diva 3) Sidefeed Warm White 3000K 24V 188mm  
3W 225 lm

| Model Number           | Voltage Input (V) | Power Input (W) | A mm   | B mm   | C mm  | D mm | E mm | F mm | G mm |
|------------------------|-------------------|-----------------|--------|--------|-------|------|------|------|------|
| NDP1-Cob9(6-24V-C90    | DC24              | .5              | 33.2   | 38.3   | 55.12 | 12   | 12.6 | 10.6 | 11.5 |
| NDP1-H-Cob9(6-24V-C90  | DC24              | 1               | 94.7   | 99.8   | 116.9 | 12   | 12.6 | 10.6 | 11.5 |
| NDP3-H-Cob9(6-24V-C90  | DC24              | 3               | 186.2  | 193.3  | 210.4 | 12   | 12.6 | 10.6 | 11.5 |
| NDP4-H-Cob9(6-24V-C90  | DC24              | 4               | 279.2  | 284.3  | 301.4 | 12   | 12.6 | 10.6 | 11.5 |
| NDP7-H-Cob9(6-24V-C90  | DC24              | 7               | 558.7  | 563.8  | 580.9 | 12   | 12.6 | 10.6 | 11.5 |
| NDP11-H-Cob9(6-24V-C90 | DC24              | 11              | 837.7  | 842.8  | 859.9 | 12   | 12.6 | 10.6 | 11.5 |
| NDP15-H-Cob9(6-24V-C90 | DC24              | 15              | 1116.8 | 1121.9 | 1139  | 12   | 12.6 | 10.6 | 11.5 |

