



## RIGEL50 WH50D73K

7W 3000K Warm White 50° White

Quicklink: Q6E5E

### General

Colour	White
Construction	Metal
Dimmable	Yes
IP Rating	IP44

### Dimensions

Cut Out	67.2mm (Diameter)
Diameter	51mm
Minimum Ceiling Depth	64mm
Vertical Rotation	30°

### Electrical

Maximum Wattage	7W
-----------------	----

### Light Characteristics

Beam Angle	50°
Colour Rendering Index	90
Colour Temperature	3000K Warm White
Lumens	883 lm
Lumens Per Watt	126 lm/W

The **Rigel 50 Adjustable** is a miniature, fire-rated downlight designed for precise, directional lighting in a compact, unobtrusive form. Despite its exceptionally small size, it delivers a powerful lumen output with CRI 90+ for outstanding colour accuracy and clarity. Its smooth adjustable tilt makes it ideal for highlighting walls, artwork, niches or architectural features, providing subtle yet effective accent lighting for premium residential and commercial interiors.

Built around a miniature integrated LED module, it requires no lamp replacement and ensures long-life, consistent performance. The plaster-in housing allows the downlight to sit perfectly flush within the ceiling, creating a seamless, minimalist finish that blends effortlessly into the surrounding architecture. Its advanced anti-glare optical design ensures comfortable, controlled illumination, while the compact and smart plug and play construction makes installation straightforward.

**Please note: This fitting requires a separate driver, available in the Linked Items section.**

# Rigel Trimless

Rigel 50 Fire-Rated Adjustable 883lm Downlight  
7W 3000K Warm White 50° White



**MR. RESISTOR**<sup>®</sup>  
Lighting Specialist Est. 1968

RIGEL 50 with 7WModule

