




RIGEL40 RD A 24D727K

7W 2700K Warm White 24° White
Quicklink: Q6E6A

General

Colour	White
Construction	Aluminium
Dimmable	Yes
IP Rating	IP44

Dimensions

Cut Out	62mm (Diameter)
Diameter	42mm
Minimum Ceiling Depth	70mm
Vertical Rotation	30°

Electrical

Maximum Wattage	7W

Light Characteristics

Beam Angle	24°
Colour Rendering Index	90
Colour Temperature	2700K Warm White
Lumens	883 lm
Lumens Per Watt	126 lm/W

The **Rigel 40 Adjustable** is a miniature, fire-rated downlight designed for precise, directional lighting in a compact, unobtrusive form. Despite its exceptionally small size, it delivers a powerful lumen output with CRI 90+ for outstanding colour accuracy and clarity.


Its smooth adjustable tilt makes it ideal for highlighting walls, artwork, niches or architectural features, providing subtle yet effective accent lighting for premium residential and commercial interiors.

Built around a miniature integrated LED module, it requires no lamp replacement and ensures long-life, consistent performance. The plaster-in housing allows the downlight to sit perfectly flush within the ceiling, creating a seamless, minimalist finish that blends effortlessly into the surrounding architecture. Its advanced anti-glare optical design ensures comfortable, controlled illumination, while the compact and smart plug and play construction makes installation straightforward.

Please note: This fitting requires a separate driver, available in the Linked Items section.

t: +44 (0)20 8874 2234 e: info@mr-resistor.co.uk **www.mr-resistor.co.uk**

RIGEL 40Adjustable with 7WModule



t: +44 (0)20 8874 2234 e: info@mr-resistor.co.uk www.mr-resistor.co.uk