



MLSA360NP BLK

Black

Quicklink: Q6E72

General

Colour	Black
IP Rating	IP55
Weight	220g

Dimensions

Depth	134mm
Height	74mm
Width	72mm

Electrical

Amperage	10A
Maximum Wattage	400W
Voltage	240V AC

The Timeguard MLSA360NP Multiway Mounting PIR Light Controller offers reliable, energy-efficient motion-activated lighting with a wide 200° front detection range up to 12m and 360° downward anti-creep coverage for enhanced security. Designed for flexible installation—ceiling, surface, internal or external corner mount—it features adjustable 1–20 minute timer, 10–1000 lux control, and an IP55 weatherproof rating, making it ideal for both indoor and outdoor use.

Key Features

- Manual override function
- 200° detection angle / 12 meters frontal detection coverage, with 360° Anti-creep detection Ø 5 meters at 25m mounting height
- Sensor head adjustable by 90° horizontally and 30° downward
- Suitable for 2000W resistive, 600W LED or 400W inductive (fan) loads
- Multiple mounting options – surface, ceiling, inner and outer corner mounting
- Easy installation with 'Fast-fix Terminal Block' connection
- Pulse function supports staircase timer operation
- IP55 Ingress protection rating

Technical Specifications

- Setting Type: Dial
- Approved Mounting Height (m): 2.5m
- Number of Channels: 1
- Switch Rating: 2000W High Voltage Halogen; 1000W Low Voltage Halogen; 1000VA / 900W Fluorescent; 900VA / 100uF Energy Saving; 600VA / 400W LED Lighting; 10A at 230V AC
- ON Time Adjustment: 1 to 20 minutes
- LUX Level: 10 to 1000
- Permanent ON Facility: Yes (Pulse Override)
- Dusk Till Dawn Mode: Yes
- Multiple Unit Support: Yes (up to 4 units in parallel)
- Cable Entry: Back entry and bottom entry (knockouts)

Surface Mounted Sensors

Multiway Mounting PIR Light Controller

Black



MR. RESISTOR®
Lighting Specialist Est. 1968

