



NTT05

Quicklink: Q6E73

General

Colour	White
IP Rating	IP20
Weight	197g

Dimensions

Depth	47mm
Height	120mm
Width	74mm

The Timeguard **NTT05 24-Hour Slimline Timeswitch** offers simple, reliable daily control with 96 quick-set segments for up to 48 ON/OFF programmes, ideal for lighting, heating, and appliances. Featuring clear LED status indicators, a user-friendly traffic-light mode selector, voltage-free contacts, and a slim, surface-mounted design, it delivers dependable, flexible scheduling for homes and businesses.

Key Features

- 96 Quick-Set Segments for up to 48 ON/48 OFF Programmes Per 24 Hrs
- Red LED 'Mains ON' & Green LED 'Output'
- 'Traffic Light' Slide Switch for Easy ON (green), Auto (green & red) and OFF (red) Mode Indication
- Switches ON & OFF At Preset Times
- Captive Segment Dial
- Permanent ON/OFF Control
- Voltage Free Contacts

Technical Specification

- Setting Type: Segment
- Program Modes: 24-Hour
- Voltage-Free Contacts: Normally Open, Normally Closed (Changeover)
- Mounting Hole Centres: 90mm
- Standby Consumption: <1.43W
- Number of Channels: 1
- Switch Rating: 16A resistive; 750W halogen/fluorescent; 100W CFL; 100W LED
- Shortest Switching Time: 15 minutes (1 segment = 15 min)
- Programmable Slots: 48 ON / 48 OFF (96 segments)
- Permanent ON Facility: Yes (Slider Switch)
- Cable Capacity: 1.5-2.5mm² flexible cable
- Cable Entry: Back entry + bottom entry (knockouts)

Time Clocks

24 Hour Slimline General Purpose Timeswitch



MR. RESISTOR[®]
Lighting Specialist Est. 1968

