

ELED-10-C100/450

4.2W-10W 100mA-450mA

Quicklink: Q6E8B

General

Dimmable Yes
IP Rating IP20

Dimensions

Height 20mm
Length 135mm
Width 30mm

Electrical

Amperage 100mA, 150mA,
200mA, 250mA,
300mA, 350mA,
400mA, 450mA

Maximum Wattage 10W
Minimum Wattage 4.2W

ELED-10-C100/450DP2 is a compact and highly versatile 10W DALI-2 constant current LED driver designed for intelligent and energy-efficient lighting systems. With a wide 100–277VAC input range and multiple selectable output currents (100–450mA), it delivers reliable, stable performance across a broad range of LED luminaires.


Equipped with both DALI-2 and Push dimming, the driver enables smooth, flicker-free light control from 0–100%, ensuring seamless integration into modern smart lighting environments.

- 100 mA (4.2W)
- 150mA (6.3W)
- 200mA (8.3W)
- 250mA (10W)
- 300mA (10W)
- 350mA (10W)
- 400mA (10W)
- 450mA (10W)




Dimming Operation


DALI Dimming Wiring Diagram1



DALI Dimming Wiring Diagram2



DALI Dimming Wiring Diagram3



Push-Dimming Wiring Diagram 1

