

# Recessed Sensors

PIR Mini Smart Ceiling Flush Mount Occupancy Detector  
DALI



## ISI MNPIR5MDALI

DALI  
Quicklink: Q6F20

### General

|           |       |
|-----------|-------|
| Colour    | White |
| Dimmable  | Yes   |
| IP Rating | IP40  |
| Weight    | 850g  |

### Dimensions

|                       |                 |
|-----------------------|-----------------|
| Cut Out               | 40mm (Diameter) |
| Diameter              | 46.5mm          |
| Minimum Ceiling Depth | 60mm            |

### Electrical

|          |      |
|----------|------|
| Amperage | 16mA |
| Voltage  | 240V |

This flush mounted ISI-MNPIR5MDALI is suitable for easy mounting through a 38/40mm diameter hole into a ceiling void which is at least 60mm deep.. Configurable for any room occupancy style, via the free to download DANLERS ISI APP on Google Play or Apple APP Store. These product include a person detector and an adjustable photocell override. Designed for mounting through suspended or plasterboard ceilings or for fitting into luminaires. Includes power pack with connector.

- Detection Zone: 360°
- Max. Detection Area: Up to 7mdiameter at 2.4m mounting height
- Max. Mounting Height: 5m
- Photocell range: 5-2000 lux and inactive
- Time lag range: 10 seconds to 3 hours
- Dimensions: Detector head 61.7mm x 46.5mm diameter. Fits into a 38-40mm diameter cut-out. Power pack 118.2 x32.5 x 32.5 mm
- Up to 8 ballasts (16mA total)
- **Please note this sensor is only compatible to work with DANLERS ISI enabled app**

# Recessed Sensors

PIR Mini Smart Ceiling Flush Mount Occupancy Detector  
DALI

