



ISI MNPIR5MSW

Switching

Quicklink: Q6F21

General

Colour	White
Dimmable	Yes
IP Rating	IP40
Weight	102g

Dimensions

Cut Out	40mm (Diameter)
Diameter	46.5mm
Minimum Ceiling Depth	60mm

Electrical

Amperage	2A
Maximum Wattage	450W
Voltage	240V

This flush mounted ISI-MNPIR5MSW is suitable for easy mounting through a 38/40mm diameter hole into a ceiling void which is at least 60mm deep. Configurable for any room occupancy style, via the free to download DANLERS ISI APP on Google Play or Apple APP Store. These products include a person detector and an adjustable photocell override. Designed for mounting through suspended or plasterboard ceilings or for fitting into luminaires. Includes power pack with connector.

- Detection Zone: 360°
- Max. Detection Area: Up to 7mdiameter at 2.4m mounting height
- Max. Mounting Height: 5m
- Photocell range: 5-2000 lux and inactive
- Time lag range: 10 seconds to 3 hours
- Dimensions: Detector head 61.7mm x 46.5mm diameter. Fits into a 38-40mm diameter cut-out. Power pack 118.2 x 32.5 x 32.5 mm
- Up to 2A (450W) LED, Mi load 2W resistive
- **Please note this sensor is only compatible to work with DANLERS ISI enabled app**

Recessed Sensors

PIR Mini Smart Ceiling Flush Mount Occupancy Detector
Switching



MR. RESISTOR[®]
Lighting Specialist Est. 1968

