

Recessed Sensors

PIR Smart Ceiling Flush Mounted Occupancy Detector
0-10V



ISI CEFL10V

0-10V
Quicklink: Q6F22

General

Colour	White
IP Rating	IP40
Weight	970g

Dimensions

Cut Out	75mm (Diameter)
Diameter	85mm
Length	79mm
Minimum Ceiling Depth	78mm

Electrical

Amperage	40mA
Voltage	240V

This flush mounted ISI-CEFL10V is suitable for easy mounting through a 73/75mm diameter hole into a ceiling void which is at least 78mm deep. Configurable for any room occupancy style, via the free to download DANLERS APP on Google Play or Apple APP Store. These product include a person detector and an adjustable photocell override. Designed for mounting through suspended or plasterboard ceiling.

- Detection Zone: 360°
- Max. Detection Area: Up to 7mdiameter at 2.4m mounting height
- Max. Mounting Height: 5m
- Photocell range: 5-2000 lux and inactive
- Time lag range: 10 seconds to 3 hours
- Dimensions: 79mm x 85mm diameter. Fits into a 73-75mm diameter cut-out
- 40mA (maximum 20 ballasts)
- **Please note this sensor is only compatible to work with DANLERS ISI enabled app**

Recessed Sensors

PIR Smart Ceiling Flush Mounted Occupancy Detector
0-10V

