

# Niche

DL7002 Recessed Round

Silver Amber

---



## DL7002A1 SIL/AMB

Silver Amber

Quicklink: QE30

---

### General

Colour	Silver
Construction	Anodised Aluminium
IP Rating	IP20

### Dimensions

Cut Out	38mm (Diameter)
Depth	31mm
Diameter	42mm

### Electrical

Amperage	350mA
Maximum Wattage	1W

The **DL7002 Recessed Round** is a small, round, recessed LED fitting. It can be used in the ceiling or walls. It has a high power 1 watt LED. This fitting must be used with a LED power supply.

Many different LED power supplies are available that allow you to achieve more with your lighting. Simply select the correct wattage depending on how many total LED fittings it will be connected to.

### LED Driver Options

- LED Driver (Switching) - Use this driver for on/off control. Cannot be used for dimming.
  - LED Driver (Dimming) - For use with nearly all domestic dimming lighting. Most resistive dimmers have a minimum load of 60W, therefore ensure that if this not met, a dummy load is added to the circuit, such as a mains voltage halogen fitting.
  - LED Driver (1-10V) - For use with 1-10V dimmer modules or 1-10V control systems. This type of dimming does not have a minimum load.
  - Wise Chameleon (Dimming + Wireless) - This controller can be used for both switching and dimming. Additionally, this unit can communicate via radio and external push buttons, allowing you to wirelessly control your fitting. Note that an additional 24V LED driver is required to power the Wise Chameleon pack.
  - DMX (Dimming + Channel Control) - This transformer can be used for both switching and dimming as well as being fully addressable and compatible with the DMX control standard.
-